


# Topgard® Protective Helmets



Topgard Slotted Caps and Non-Slotted Hats are built for use by utilities and other industries where head protection with dielectric protection is necessary. Limited resistance to top impact or penetration is retained over a wide range of temperatures.

Topgard Caps and Hats meet all applicable requirements for a Type I helmet (top impact) as outlined in ANSI/ISEA Z89.1-2009 (Class E) and CSA Z94.1-2005 (Class E). These caps and hats also meet the ANSI/ISEA Z89.1-2009 voluntary standard for low temperature [LT] and reverse donning. Look for the official reverse donning logo  to determine if your hardhat may be worn backwards without voiding approvals.

MSA can customize your helmets with your company logo and choice of reflective striping. For more information regarding logos and stripes, contact **MSA Logo Express at 1.800.MSA.LOGO.**

## Ordering Information

Topgard Helmet Assemblies				
Color	Topgard Slotted Cap		Topgard Non-slotted Hat	
	w/1-Touch® Suspension	w/Fas-Trac® Suspension	w/1-Touch Suspension	w/Fas-Trac Suspension
White	454728	475385	454719	475393
Yellow	454721	475378	454712	475387
Gray	454722	475379	454713	•
Blue	454723	475380	•	•
Orange	454725	475382	•	•
Green	454726	475383	•	•
Red	454726	475384	•	•
Bright Orange	•	804396	•	804397
White with lamp bracket and cord holder	448914	•	•	•

## Replacement Suspension

1-Touch Suspension (6 <sup>1</sup> / <sub>2</sub> -8)	10061127
Fas-Trac Suspension (6 <sup>1</sup> / <sub>2</sub> -8)	473333
Swing-Ratchet Suspension (6 <sup>1</sup> / <sub>2</sub> -7 <sup>5</sup> / <sub>8</sub> )	816648

**Note:** this bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



ID 0612-06-MC / July 2009

© MSA 2009 Printed in U.S.A.

**Corporate Headquarters**  
P.O. Box 426, Pittsburgh, PA 15230 USA  
Phone 412-967-3000  
[www.MSAnet.com](http://www.MSAnet.com)

**U.S. Customer Service Center**  
Phone 1-800-MSA-2222  
Fax 1-800-967-0398

**MSA Canada**  
Phone 416-620-4225  
Fax 416-620-9697

**MSA Mexico**  
Phone 01 800 672 7222  
Fax 52-44 2227 3943

**MSA International**  
Phone 412-967-3354  
FAX 412-967-3451

**MSA**  
The Safety Company